

PL-2005

Fugitive Adhesive



Stick with Valco Melton™

PRODUCT TYPE:

Fugitive Adhesive

PHYSICAL PROPERTIES	
Appearance	Amber
Specific Gravity	0.94
Form	Pellet
Bond	Light
Peel Strength	Medium
Viscosity	5,000 cps at 325° F
	1,700 cps at 350° F



OPERATING TEMPERATURES:

Target: 325° F
Typical: 315° F to 350° F

SUGGESTED USE:

- Product Attaching / Bonding
- Bonding of Metal Alloys
- Bonding of Paper and Plastic

PRODUCT FEATURES:

- Quick setting ideal for most applications
- "Peelable" or removable once set
- Excellent staining and bleed resistance
- No residue or ghosting on steel and glass
- Meets composition requirements of Indirect Food Additives Regulation 21 CFR 175.105

OPERATING CONDITIONS:

- Suitable for all gear driven pumps
- Suitable for piston pumps with spring loaded ball checks
- Applied with any standard pneumatic or electric applicator
- Air open/air close application reduces stringing and trailing
- Suitable for wheel based applications

PRECAUTIONS:

- Material applied hot - appropriate clothing or eye protection should be used.
- Use with adequate ventilation to remove melt fumes or vapors being generated.
- Keep containers and pre-melters covered.
- Do not mix with other adhesives.



ISO 9001

QUALITY SYSTEMS

Ordering Information:

Part Number: 713xx077, 25 lb. box



For more information visit www.valcomelton.com, or contact your local representative.

World Headquarters: USA, Cincinnati, Ohio (Corporate Offices) • Tel: 513.874.6550 • Fax: 513.874.3612 • info@valcomelton.com

European Headquarters: Spain, Navarra • Tel: +34.948.321.580 • Fax: +34 948 326 584 • melton@melton.es

Asian Headquarters: China, Xiamen, Fujian • Tel: +86.592.591.7854 • Fax: +86.592.591.7834 • china@valcomelton.com

www.valcomelton.com • Serving Over 52 Countries Worldwide.

