

G-R 1994

Synthetic Resin




Stick with Valco Melton™

PRODUCT TYPE:

Synthetic Resin

PHYSICAL PROPERTIES	
Appearance	White, fluid product
Solids	Approximately 20 - 28%
Viscosity	Approximately 300 - 450 cps
pH	Approximately 5.0 - 6.8
LBS/gallon	Approximately 8.5 - 8.7



SUGGESTED USE:

Graphic arts applications, normal weight uncoated stock

OPERATING CONDITIONS:

- Fine-line and non-contact extrusion systems
- Stir thoroughly before using
- Ready-for-use viscosity as supplied
- Wet film soluble in warm water
- Dry film soluble in water

PRECAUTIONS:

- Protect from temperatures below 40° F.
- Rotate stock, using oldest material first.
- Keep covered to prevent drying out and contamination.
- Do not mix with other adhesives.

PRECAUTIONS:

- Protect from temperatures below 40° F
- Rotate stock, using oldest material first
- Keep covered to prevent drying out and contamination
- Do not mix with other adhesives

ISO 9001

QUALITY SYSTEMS

Ordering Information:

Part Number: 713xx029, 5-gallon pail
713xx030, 55-gallon drum
713xx031, 300-gallon tote



For more information visit www.valcomelton.com, or contact your local representative.

World Headquarters: USA, Cincinnati, Ohio (Corporate Offices) • Tel: 513.874.6550 • Fax: 513.874.3612 • info@valcomelton.com

European Headquarters: Spain, Navarra • Tel: +34.948.321.580 • Fax: +34 948 326 584 • melton@melton.es

Asian Headquarters: China, Xiamen, Fujian • Tel: +86.592.591.7854 • Fax: +86.592.591.7834 • china@valcomelton.com

www.valcomelton.com • Serving Over 52 Countries Worldwide.

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers before using any product in full scale production make their own test to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. No representative of ours has any authority to waive or change the foregoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, covered by any patent, without the authority from the owner of this patent. We also expect purchasers to use our products in accordance with the guiding principles of the Chemical Manufacturers Association's Responsible Care program.
© Valco Cincinnati, Inc. All Rights Reserved. Valco Cincinnati reserves the right to make design changes between printing.

